

# > 6200

## Automated Pitot Static Tester



### DESCRIPTION

The Model 6200 is used to perform leak-checks and accuracy checks on the Pitot Static systems of helicopters & non-RVSM aircraft. The 6200 is WiFi-enabled. Accuracy checks are typically performed on altimeters, airspeed indicators and VSI's. The high accuracy of the Pitot output is ideally suited for checks at low airspeeds.



### KEY FEATURES

- Altitude offset correction
- Programmable Limits
- Protection against negative airspeed
- Self Test checks all internal functions
- Automatic ambient-pressure sensing
- Manual vent valves for emergency venting
- Independent or simultaneous leak-checking on Pitot and Static outputs
- Instant leak-rate display enhances leak-detection
- 5.83" ultra-bright sunlight-readable color display
- Strong pumps have minimum 5000-hour life
- Pull-out handle and wheels for easy portability



### SIZE

Main unit: 56 x 35.6 x 22.8 (cm)  
1.84 x 1.16 x 0.75 (ft)



### WEIGHT

Main unit: 13.6 (kg)  
30.0 (lbs)



### APPLICABILITY

AS332, AS350, AS355, AS365, AS366, AS532, AS550, AS555, AS565, EC120, EC130, EC155, EC175, EC225, EC725, SA330, SA360.

### CONTACT US

+33 467 455 564

150, Rue Maurice Béjart - 34080 - Montpellier, FRANCE  
contact@kit-aero.com / www.kit-aero.com

