## > G85D-S

# Pneumatic Hydraulic Hand Riveter





#### **DESCRIPTION**

The G85D-S pneumatic-hydraulic lockbolt installation tool is a heavy duty production tool designed for high speed, reliable installation of the most popular sizes of aircraft lockbolts. This "split" unit helps accessing tight areas and reduces operator fatigue. Its durable, all metal housing makes this tool very robust for use in a shop environment.

This tool installs all 3/16", 1/4" and 5/16" diameter Lockbolts® (any material type) and 3/8" diameter aluminum lockbolts. It can also install selected blind bolts and blind rivets.



### **KEY FEATURES**

- NATO Stock Number: 5130-01-580-1287
- Air Pressure 6.2 bar (90 PSI) Min. / 7,6 bar (110 PSI) Max.
- Stroke 18,3 mm (0.720 in.)
- Pulling Force 31,1 kg (7,000 lbs.) @ 6,2 bar (90 PSI),
- Noise level 76.7 dB (A)
- Vibrtion less than 2.5 m/s2
- Air Consumption 7.65 L/cycle (0.27 SCF/cycle)



**►** SIZE

Not Applicable



**WEIGHT** 

8.75 (kg) 19.3 (lbs)



#### **APPLICABILITY**

All aircrafts